

AMENDED CLAIMS

1. (previously presented) A mounting apparatus for mounting an associated can-type capacitor to a sheet metal portion of an associated electrical device housing, the mounting apparatus comprising:

a clip arranged on the sheet metal portion; and

a receiving region arranged on the sheet metal portion, having a slot formed into the sheet metal portion, the receiving region receiving an edge of the capacitor, the edge comprising a portion of a rim of the capacitor, and cooperating with the clip to at least partially secure the capacitor to the sheet metal portion, wherein the portion of the rim is inserted into the slot when the capacitor is positioned at an angle relative to the sheet metal portion.

2. (canceled)

3. (original) The mounting apparatus as set forth in claim 1, wherein:

The edge of the capacitor comprises a portion of a rim of the capacitor; and

the receiving region includes a slot formed into the sheet metal portion that receives the portion of the rim of the capacitor.

4. (previously presented) The mounting apparatus as set forth in claim 1, wherein:

the rim of the capacitor includes a crimped region formed during crimping of a lid to the can-type capacitor housing.

5. (canceled)

6. (original) The mounting apparatus as set forth in claim 1, further comprising:

BEST AVAILABLE COPY

at least one wire tie that passes through at least one hole formed into the sheet metal portion and around the capacitor to retain the capacitor against the sheet metal portion, said at least one wire tie cooperating with said receiving region and said clip to operatively secure the capacitor to the sheet metal portion.

7. (previously presented) A mounting apparatus for mounting an associated capacitor within the housing of an associated electrical apparatus, the mounting apparatus comprising:

a clip that secures to a portion of the capacitor; and

at least one wire tie that at least partially encircles the capacitor and that cooperates with at least one hole formed into the housing in securing the capacitor to the housing, wherein

the capacitor includes a cylindrical housing having a crimped lip, and

the portion of the capacitor includes a portion of the crimped lip.

8. (original) The mounting apparatus as set forth in claim 7, wherein:

the at least one wire tie includes two wire ties, and the at least one hole includes a plurality of holes.

9. (canceled)

10. (canceled)

11. (previously presented) The mounting apparatus as set forth in claim 7, wherein:

the clip secures the capacitor against movement parallel to the cylindrical axis.

12. (original) The mounting apparatus as set forth set

BEST AVAILABLE COPY

forth in claim 11, wherein the clip includes:

- a tab affixed to the housing; and
- a slot formed into the housing that receives the portion of the crimped lip.

13. (original) The mounting apparatus as set forth in claim 12, wherein:

- the tab is integrally formed into a sheet metal portion of the associated housing.

14. (canceled)

15. (currently amended) The lighting fixture as set forth in ~~claim 14~~ claim 16, wherein:

- the at least one wire tie comprises two wire ties.

16. (currently amended) ~~A~~ The lighting fixture ~~as set forth in claim 14, wherein comprising:~~

a socket for operatively receiving a light bulb, lamp, or light source;

a the cylindrical capacitor that includes a rim extending beyond the main cylindrical body of the capacitor; and

at least one wire tie at least partially securing the capacitor to the lighting fixture; and

~~the mounting surface of the lighting fixture includes a retaining clip arranged thereon~~ on the mounting surface of the lighting fixture, the lighting fixture having and a slot formed therein, said retaining clip cooperating with said slot to partially secure at least a portion of the capacitor rim, said secured rim portion further cooperating with the at least one wire tie to operatively secure the capacitor to the mounting surface of the lighting fixture.

17. (original) The lighting fixture as set forth in claim 16, wherein:

BEST AVAILABLE COPY

the retaining clip includes a retaining clip formed integrally into the mounting surface of the lighting fixture.

18. (original) The lighting fixture as set forth in claim 16, wherein:

the retaining clip includes a partially cut-out portion of the mounting surface of the lighting fixture, said partially cut-out portion being formed into the retaining clip.

19. (original) The lighting fixture as set forth in claim 16, wherein the partial securing of at least a portion of the capacitor rim includes:

inserting the rim portion into the slot, the inserting occurring with the capacitor positioned at an angle relative to the mounting surface; and

rotating the capacitor against the mounting surface, said rotating occurring about the inserted rim portion and effectuating a partial securing of the rim between the retaining clip and at least one edge of the slot.

20. (original) The lighting fixture as set forth in claim 16, wherein:

the capacitor rim includes a connecting portion of a capacitor housing, said connecting portion corresponding to a crimped region that connects a lid portion of the capacitor housing to a cylindrical portion of the capacitor housing.